

# Material Safety Data Sheet

Page 1 of 7

Issue date: December 2015

## NITROPAC BLENDING CLEAR INK

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** NITROPAC BLENDING CLEAR INK

**Manufacturer's Product Code:** HV1010

**Use:** To mix with bases to make printing inks.

**DYEPAC LIQUID INKS PTY. LTD.**

**A.C.N. 009 995 215**

**A.B.N.94 009 995 215**

**29 ENTERPRISE STREET**

**CLEVELAND QLD 4163**

**Phone: (07) 3821 0899 FAX: (07) 3821 0788**

**e-mail : [info@dyepac.com.au](mailto:info@dyepac.com.au)**

**Web : <http://www.Dyepac.com.au>**

**Emergency Advice All Hours:**

### 2. HAZARDS IDENTIFICATION

HAZARDOUS ACCORDING TO ASCC/NOHSC/EU CRITERIA

**Hazard Category:** Irritant (Xi), Highly Flammable (F)

**Hazard Classification:** HAZARDOUS SUBSTANCE, DANGEROUS GOODS

#### RISK PHRASES

R11 Highly flammable

R41 Risk of serious damage to eyes.

R67 Vapours may cause drowsiness and dizziness.

#### SAFETY PHRASES

S7 Keep container tightly closed.

S16 Keep away from sources of ignition - No smoking.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

#### Road Transport (ADR/RID)

**UN Number:** 1210

**Proper Shipping Name:** PRINTING INK

**Dangerous Goods Class:** 3

**Packing Group:** II

**Poison Schedule:** None allocated [Aust].

#### Warning Statement:

Highly flammable liquid. Avoid all sources of ignition, heat and sources of heat. Liquid will cause serious damage to eyes.

# Material Safety Data Sheet

Page 2 of 7

Issue date: December 2015

## NITROPAC BLENDING CLEAR INK

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| SUBSTANCE NAME | Proportion | CAS Number |
|----------------|------------|------------|
| NITROCELLULOSE | 1 to 10 %  | 9004-70-0  |
| ETHANOL        | 10 to 30 % | 64-17-5    |
| n-PROPANOL     | 10 to 30 % | 71-23-8    |

All other ingredients not hazardous according to ASCC/NOHSC/EU Criteria.

### 4. FIRST AID MEASURES

#### Swallowed:

If swallowed, **DO NOT** induce vomiting. If victim conscious, give 1 to 2 glasses of water to drink. Seek urgent medical assistance.

#### Eye:

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes..

#### Skin:

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

#### Inhaled:

Remove victim to fresh air. Apply resuscitation if victim is not breathing - Administer oxygen if breathing is difficult. Transport to hospital or doctor immediately.

#### First Aid Facilities:

Eye wash fountain, safety shower and normal wash room facilities.

#### Advice to Doctor:

Treat symptomatically.

**For advice, contact Poisons Information Centre**

**In Australia call Tel: 13 1126**

**In New Zealand Tel: 034747000**

### 5. FIRE-FIGHTING MEASURES

#### Fire/Explosion Hazard

**SUITABLE EXTINGUISHING MEDIA:** Foam, dry chemical or carbon dioxide.

**HAZARDS FROM COMBUSTION PRODUCTS:** Decomposes on heating emitting oxides of carbon and noxious smoke.

**PRECAUTIONS FOR FIRE FIGHTERS AND SPECIAL PROTECTIVE EQUIPMENT:** Self-contained breathing apparatus (SCBA) required for fire-fighting personnel. If possible to do so safely, shut off fuel to fire. Avoid spreading burning liquid with water used for cooling fire exposed containers when using water spray, boil-over may occur when the product temperature reaches the boiling point of water, thereby resulting in re-ignition.

**HAZCHEM CODE:** 3[Y]E [Aust]

#### FLAMMABILITY

This material is a HIGHLY FLAMMABLE liquid. Avoid all sources of ignition, heat and naked flames.

**Flash Point:** 13°C

**Flammability Limits:** LEL: 1.0% UEL: 8.0%

# Material Safety Data Sheet

Page 3 of 7

Issue date: December 2015

## NITROPAC BLENDING CLEAR INK

### 6. ACCIDENTAL RELEASE MEASURES

**Emergency Procedures:**

Highly flammable liquid. Avoid all sources of ignition. Keep unnecessary people away; Isolate hazard area and deny entry. Ventilate area. Wear suitable protective equipment as outlined under personal protection in this MSDS.

**Methods and Materials for Containment and Clean Up Procedures:**

Throw diatomaceous earth onto spill. **DO NOT** use sawdust. Use non-sparking tools or HEPA vacuum system to pick up. Place into labeled drum(s) for later disposal. If risk of fire, blanket the spill with foam or use water fog to disperse vapour clouds. Consult an expert regarding disposal of this product.

**Emergency information(Transport):**

Dangerous Goods - Initial Emergency Response Guide (SAA/SNZ HB76:2004)

For LIQUIDS - **Highly Flammable**, Guide No: 14

### 7. HANDLING AND STORAGE

**Precautions for Safe Handling:**

Highly flammable liquid. Avoid ignition sources. Do not get in eyes. Avoid direct or prolonged contact with skin. Provide adequate ventilation.

**Conditions for Safe Storage:**

Keep containers tightly closed, when not using the product. Store in original packages as approved by manufacturer. Store in an area that is dry and well-ventilation away from ignition sources. Store at ambient temperatures. The floor of the depot should be impermeable. Store away from oxidizing agents. For further information please refer to the Engineering Controls of this MSDS.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Standards**

No exposure standards are available for this product, however, the following exposure standards have been assigned by [NOHSC] to the following components of the product:

***NITROCELLULOSE***

[NOHSC]

|                |                        |
|----------------|------------------------|
| [TWA] 400 ppm  | 983 mg/m <sup>3</sup>  |
| [STEL] 500 ppm | 1230 mg/m <sup>3</sup> |

***ETHANOL***

[NOHSC]

|                 |                         |
|-----------------|-------------------------|
| [TWA] 1,000 ppm | 1,880 mg/m <sup>3</sup> |
|-----------------|-------------------------|

**References:** H

***n-PROPANOL***

[NOHSC]

|                |                       |
|----------------|-----------------------|
| [TWA] 200 ppm  | 492 mg/m <sup>3</sup> |
| [STEL] 250 ppm | 614 mg/m <sup>3</sup> |

**Notices:** Sk

**References:** H

**Sk Notation:**

# Material Safety Data Sheet

Page 4 of 7

Issue date: December 2015

## NITROPAC BLENDING CLEAR INK

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION (Continued)

For most substances in the occupational setting, the main route of entry into the body is via inhalation. However, some substances can readily penetrate the intact skin and thus become absorbed into the body, with resultant toxic effects.

#### Engineering Controls

Highly flammable liquid. Maintain adequate ventilation at all times. Prevent accumulation of vapours in hollows or sumps. Eliminate any sources of ignition.

#### Personal Protection Equipment

**GLOVES:** Neoprene or nitrile.

**EYES:** Chemical goggles or spectacles with side shields to protect eyes.

**RESPIRATORY PROTECTION:** Avoid breathing of vapours. Filter capacity and respirator type depends on exposure levels and type of contaminant. Select and use respirators in accordance with AS/NZS 1715. If contaminants reach exposure standards the use of a suitable respirator fitted with an organic vapour cartridge is recommended.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Clear coloured liquid with alcohol odour

**Boiling Point:** 70 - 110 °C

**Vapour Density:** Heavier than air

**Specific Gravity:** 1.00

**Flash Point:** 13°C

**Flammability Limits:** LEL: 1.0% UEL: 8.0%

**Solubility in Water:** Insoluble

#### Other Properties

**pH:** Not available.

### 10. STABILITY AND REACTIVITY

#### CHEMICAL STABILITY:

Stable under normal conditions of use.

#### CONDITIONS TO AVOID:

Ignition sources and mixing with incompatibles.

#### INCOMPATIBLE MATERIALS:

Oxidizing agents.

#### HAZARDOUS DECOMPOSITION PRODUCTS:

Decomposes on heating emitting oxides of carbon and noxious smoke.

#### HAZARDOUS REACTIONS:

Will not occur.

### 11. TOXICOLOGICAL INFORMATION

No adverse health effects are expected, if the product is handled in accordance with this Material Safety Data Sheet and the product label. Symptoms and effects that may arise if the product is mishandled and overexposure occurs are:

# Material Safety Data Sheet

Page 5 of 7

Issue date: December 2015

## NITROPAC BLENDING CLEAR INK

### 11. TOXICOLOGICAL INFORMATION (Continued)

#### ACUTE HEALTH EFFECTS:

##### **Swallowed:**

May cause irritation to mouth, throat and stomach with effects including mucous build up, irritation to the tongue and lips and pains in the stomach, which may lead to nausea, vomiting and diarrhoea.

##### **Eye:**

Will cause severe irritation to the eyes with effects including: tearing, pain, corneal opacity and blurred vision. If prompt action is not taken permanent eye damage may occur.

##### **Skin:**

May cause irritation to the skin.

##### **Inhaled:**

Mists or vapours may cause irritation to the nose, throat and respiratory system with effects including: Dizziness, headache, coughing, loss of co-ordination and chest pains.

##### **Chronic:**

Prolonged or repeated skin contact may lead to dermatitis to some susceptible individuals. Prolonged contact may cause severe eye irritation and some form of permanent eye damage may occur. Vapours may cause drowsiness and dizziness

##### **Ethanol:**

Oral LDLo(Human): 1,400 mg/kg

Reaction: Stupor, sleepiness, headache.

Oral LD50(rat): 7,060 mg/kg

##### **n-Propanol:**

Inhalation LCLo(Rat): 4,000 ppm/4H

Oral LD50(rat): 1,870 mg/kg

EYE - STANDARD DRAIZE TEST

From the published literature a dose of 20 mg/24Hr produces a moderate reaction in the eyes of rabbits.

### 12. ECOLOGICAL INFORMATION

There is no ecological information available for this product, however for the ingredients:

The following ecological information is available for n-Propanol:

**TERRESTRIAL FATE:** When spilled on soil, n-propanol will both volatilize and leach into the ground. It will leach into groundwater.

**AQUATIC FATE:** When released into water, n-propanol will volatilize (estimated half- life approx. 6.5 days) and may biodegrade.

**ATMOSPHERIC FATE:** When released into the atmosphere, n-propanol will photodegrade by reaction with hydroxyl radicals (estimated half-life is 6.7 days).

# Material Safety Data Sheet

Page 6 of 7

Issue date: December 2015

## NITROPAC BLENDING CLEAR INK

### 13. DISPOSAL CONSIDERATIONS

Refer to appropriate authority in your State. Dispose of material through a licensed waste contractor. Advise highly flammable nature. If large amounts of the product enter waterways, sewers or streams, immediately contact the Environmental Protection Agency or your Local Waste Management Authority.

### 14. TRANSPORT INFORMATION

#### Road Transport (ADR/RID)

**UN Number:** 1210

**Proper Shipping Name:** PRINTING INK

**Dangerous Goods Class:** 3

**Packing Group:** II

#### Air Transport (ICAO/IATA)

**UN Number:** 1210

**Proper Shipping Name:** PRINTING INK

**Dangerous Goods Class:** 3

**Packing Group:** II

#### Sea Transport (IMDG)

**UN Number:** 1210

**Proper Shipping Name:** PRINTING INK

**Dangerous Goods Class:** 3

**Packing Group:** II

**EMS:** F-E,S-D

### 15. REGULATORY INFORMATION

**Poison Schedule:** None allocated [Aust]

#### Inventory Status:

Australia (AICS) Y

United States (TSCA) Y

Europe (EINECS/ELINCS) Y

Y = all ingredients are on the inventory.

**EU Label:** Irritant (Xi), Highly Flammable (F)

# Material Safety Data Sheet

Page 7 of 7

Issue date: December 2015

## NITROPAC BLENDING CLEAR INK

### 16. OTHER INFORMATION

**Date of Preparation:**

**Issue date:** December 07, 2015

**Supersedes:** August 08, 2011

**Reasons for Update:**

1. Alignment with the 2<sup>nd</sup> Edition of National Code of Practice for the Preparation of Material Safety Data Sheets [NOHSC:2001(2003)].

**Key Legend Information:**

NOHSC - National Occupational Health & Safety Commission {Formerly Worksafe}[Aust]

ASCC - Australian Safety and Compensation Council [Aust]

SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons [Aust]

TWA - Time Weighted Average [Int]

STEL - Short Term Exposure Limit [Int]

AICS - Australian Inventory of Chemical Substances

Dangerous Goods - Initial Emergency Response Guide (SAA/SNZ HB76:2004) [Aust]

EPA - Environmental Protection Agency [Int]

NIOSH - National Institute for Occupational Safety and Health [US]

TSCA - Toxic Substances Control Act [US]

OSHA - Occupational Safety and Health Administration [US]

AS/NZS 1715 - Selection, use and maintenance of respiratory protective devices. [Aust/NZ]

Hazchem Code - Fire fighters designation [Aust]

IATA - International Aviation Transport Authority [Int]

ICAO - International Civil Aviation Organization [Int]

IMO - International Maritime Organisation. [Int]

IMDG - International Maritime Dangerous Goods [Int]

United Nations Recommendations for the Transport of Dangerous Goods and Globally Harmonized System for the classification and labelling of Chemicals. [Int]

EINECS - European Inventory of Existing Commercial Chemical Substances. [Int]

ELINCS - European List of Notified Chemical Substances. [Int]

EU - European Union [Int]

ADR/RID - European Road & Rail Transport Union - [Int]

**EU Directives:** The classification criteria used, are adopted from the European Community's (EC) legislation for classifying dangerous substances. The criteria are taken from:

EC Council Directive 67/548/EEC

EC Council Directive 1999/45/EC

[Aust/NZ] = Australian New Zealand

[Int] = International

[US] = United States of America

**Principal References:**

Information supplied by manufacturer, reference sources including the public domain.

**Disclaimer**

Any advice, recommendation, information, assistance or service provided by Dyepac Liquid Inks Pty. Ltd. in relation to the goods supplied by it or their use or application is given in good faith and believed to be appropriate and reliable, however, it is provided with a disclaimer for any liability or responsibility on the part of Dyepac Liquid Inks Pty. Ltd. The customer accepts all risk and responsibility for use of the goods alone, or in combination with other products. All warranties, guarantees and conditions, other than those expressly stated and whether implied by statute, common law, custom of the trade or otherwise, are to the extent that the law permits, expressly excluded.

**END OF MSDS**