

# Material Safety Data Sheet

Page 1 of 7

Issue date: December 2015

## STENCIL KING REDUCER

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** STENCIL KING REDUCER  
**Manufacturer's Product Code:** SK

**Use:** Used to extend the life of the ink during the printing process and also aids in the drying process.

**DYEPAC LIQUID INKS PTY. LTD.**  
**A.C.N. 009 995 215**  
**A.B.N.94 009 995 215**  
**29 ENTERPRISE STREET**  
**CLEVELAND QLD 4163**  
**Phone: (07) 3821 0899 FAX: (07) 3821 0788**  
**e-mail : info@dyepac.com.au**  
**Web : http://www.Dyepac.com.au**

### 2. HAZARDS IDENTIFICATION

HAZARDOUS ACCORDING TO ASCC/NOHSC/EU CRITERIA

**Hazard Category:** Harmful (Xn), Irritant (Xi), Highly Flammable (F)

**Hazard Classification:** HAZARDOUS SUBSTANCE, DANGEROUS GOODS

#### RISK PHRASES

R11 Highly flammable  
R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.  
R36/38 Irritating to eyes and skin.

#### SAFETY PHRASES

S7 Keep container tightly closed.  
S16 Keep away from sources of ignition - No smoking.  
S36/37 Wear suitable protective clothing and gloves.  
S45 In case of accident or if you feel unwell, contact a doctor or Poisons Information Centre immediately and show this container or label.

#### Road Transport (ADR/RID):

**UN Number:** 1993  
**Proper Shipping Name:** FLAMMABLE LIQUID, N.O.S. (Contains 2-BUTOXY ETHANOL and ETHANOL)  
**Dangerous Goods Class:** 3  
**Packing Group:** II

#### Poison Schedule: S5 [Aust]

This material is a Scheduled S5 Poison and must be stored, handled and used according to the appropriate regulations.

#### Warning Statement:

Vapour and liquid is harmful by skin, inhalation and if swallowed. Liquid will cause irritation to eyes and skin. Highly flammable, avoid all sources of ignition, heat and naked flames.

# Material Safety Data Sheet

Page 2 of 7

Issue date: December 2015

## STENCIL KING REDUCER

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

SUBSTANCE NAME	Proportion	CAS Number
2-BUTOXY ETHANOL	30 to 70 %	111-76-2
ETHANOL	10 to < 30 %	64-17-5

All other ingredients determined not to be hazardous according to ASCC/NOHSC/EU criteria.

### 4. FIRST AID MEASURES

#### Swallowed:

If swallowed, **DO NOT** induce vomiting. If victim conscious, give 1 to 2 glasses of water to drink. Seek urgent medical assistance.

#### Eye:

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes..

#### Skin:

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

#### Inhaled:

Remove victim to fresh air. Apply resuscitation if victim is not breathing - Administer oxygen if breathing is difficult. Transport to hospital or doctor immediately.

#### First Aid Facilities:

Eye wash fountain, safety shower and normal wash room facilities.

#### Advice to Doctor:

Treat symptomatically.

**For advice, contact Poisons Information Centre**

**In Australia call Tel: 13 1126**

**In New Zealand Tel: 034747000**

### 5. FIRE-FIGHTING MEASURES

#### Fire/Explosion Hazard

**SUITABLE EXTINGUISHING MEDIA:** Water fog, foam, dry chemical or carbon dioxide.

**HAZARDS FROM COMBUSTION PRODUCTS:** Decomposes on heating emitting oxides of carbon and noxious smoke.

**PRECAUTIONS FOR FIRE FIGHTERS AND SPECIAL PROTECTIVE EQUIPMENT:** Self-contained breathing apparatus (SCBA) required for fire-fighting personnel. If possible to do so safely, shut off fuel to fire.

**HAZCHEM CODE:** 2[Y]E [Aust]

#### FLAMMABILITY

This material is a **HIGHLY FLAMMABLE** liquid. Avoid all sources of ignition, heat and naked flames.

**Flash Point:** < 23°C

# Material Safety Data Sheet

Page 3 of 7

Issue date: December 2015

## STENCIL KING REDUCER

### 6. ACCIDENTAL RELEASE MEASURES

**Emergency Procedures:**

Highly flammable liquid. Avoid all sources of ignition. Keep unnecessary people away; Isolate hazard area and deny entry. Ventilate area. Wear suitable protective equipment as outlined under personal protection in this MSDS.

**Methods and Materials for Containment and Clean Up Procedures:**

Throw diatomaceous earth onto spill. **DO NOT** use sawdust. **ALLOW TO ABSORB**. Use non-sparking tools or HEPA vacuum system to pick up. Place into labelled drum(s) for later disposal. If risk of fire, blanket the spill with foam or use water fog to disperse vapour clouds. Consult an expert regarding disposal of this product.

**Emergency information(Transport):**

Dangerous Goods - Initial Emergency Response Guide (SAA/SNZ HB76:2004)

For **LIQUIDS** - Highly Flammable, Guide No: 14

### 7. HANDLING AND STORAGE

**Precautions for Safe Handling:**

Highly flammable liquid. Avoid ignition sources. Do not get in eyes. Avoid direct or prolonged contact with skin. Provide adequate ventilation.

**Conditions for Safe Storage:**

Keep containers tightly closed, when not using the product. Store in original packages as approved by manufacturer. Store in an area that is dry and well-ventilation away from ignition sources. The floor of the depot should be impermeable. Store away from oxidizing agents. For further information please refer to the Engineering Controls of this MSDS.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Standards**

No exposure standards are available for this product, however, the following exposure standards have been assigned by [NOHSC] to the following components of the product:

**2-BUTOXY ETHANOL**

[NOHSC]

[TWA] 25 ppm 121 mg/m<sup>3</sup>

**Notices:** Sk

**References:** H;R

**Sk Notices:**

The adopted national exposure standards listed only consider absorption via inhalation. In some instances, special measures may be required to prevent absorption through the skin. Chemical compounds requiring such precautions are specified by the notation 'Sk'.

**ETHANOL**

[NOHSC]

[TWA] 1,000 ppm 1,880 mg/m<sup>3</sup>

**References:** H

# Material Safety Data Sheet

Page 4 of 7

Issue date: December 2015

## STENCIL KING REDUCER

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION (continued)

#### Engineering Controls

Highly flammable liquid. Maintain adequate ventilation at all times. Prevent accumulation of vapours in hollows or sumps. Eliminate any sources of ignition.

#### Personal Protection Equipment

**GLOVES:** Neoprene or nitrile.

**EYES:** Chemical goggles or spectacles with side shields to protect eyes.

**RESPIRATORY PROTECTION:** Avoid breathing of vapours. Filter capacity and respirator type depends on exposure levels and type of contaminant. Select and use respirators in accordance with AS/NZS 1715. When vapours exceed the exposure standards and there is no suitable ventilation systems then the use of a half-face respirator fitted with an organic vapour cartridge is recommended.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Water white liquid with characteristic odour.
<b>Boiling Point:</b>	>80°C
<b>Vapour Pressure:</b>	Not available.
<b>Specific Gravity:</b>	0.790
<b>Flash Point:</b>	< 23°C
<b>Flammability Limits:</b>	Not available.
<b>Solubility in Water:</b>	Completely soluble.

#### Other Properties

**Vapour Pressure:** Heavier than air.

### 10. STABILITY AND REACTIVITY

#### CHEMICAL STABILITY:

Stable under normal conditions of use.

#### CONDITIONS TO AVOID:

Ignition sources and mixing with incompatibles.

#### INCOMPATIBLE MATERIALS:

Oxidizing agents.

#### HAZARDOUS DECOMPOSITION PRODUCTS:

Decomposes on heating emitting oxides of carbon and noxious smoke.

#### HAZARDOUS REACTIONS:

Will not occur.

### 11. TOXICOLOGICAL INFORMATION

No adverse health effects are expected, if the product is handled in accordance with this Material Safety Data Sheet and the product label. Symptoms and effects that may arise if the product is mishandled and overexposure occurs are:

#### ACUTE HEALTH EFFECTS

##### Swallowed:

Harmful if swallowed. May cause irritation to mouth, throat and stomach with effects including pains in the stomach, which may lead to nausea, vomiting and diarrhoea. Swallowing large quantities of 2-butoxy ethanol may result in metabolic acidosis, hypokalemia, hemoglobinuria, and possibly coma.

# Material Safety Data Sheet

Page 5 of 7

Issue date: December 2015

## STENCIL KING REDUCER

### 11. TOXICOLOGICAL INFORMATION (continued)

**Eye:**

May cause irritation to the eyes, with effects including: tearing, pain, stinging and blurred vision.

**Skin:**

Harmful by skin contact. May cause irritation to the skin, with effects including; Redness and itchiness. 2-butoxy ethanol may be absorbed through the skin with resultant toxic effects in blood system, spleen and testes.

**Inhaled:**

Harmful if inhaled. Mists or vapours will cause irritation to the nose, throat and respiratory system with effects including: Dizziness, headache, coughing, loss of co-ordination and chest pains. 2-butoxy ethanol may affect the central nervous system.

**Chronic:**

Prolonged or repeated skin contact may lead to dermatitis. Product may also be absorbed through the skin with resultant toxic effects. Prolonged or repeated exposure may lead to irreversible damage to health. Prolonged or repeated exposure or deliberately concentrating and inhaling the vapour may result in lung function incapacity or death.

**2-Butoxy ethanol:**

Oral LD50(rat): 470 mg/kg

Inhalation LC50(rat): 450 ppm/4Hr

Dermal LD50(rabbit): 220 mg/kg

**Ethanol:**

Oral LDLo(Human): 1,400 mg/kg

Reaction: Stupor, sleepiness, headache.

Oral LD50(rat): 7,060 mg/kg

### 12. ECOLOGICAL INFORMATION

This substance may cause long term adverse effects in the environment, there is no other additional information available for this product. Avoid contaminating drains, sewers or waterways.

### 13. DISPOSAL CONSIDERATIONS

Refer to appropriate authority in your State. Dispose of material through a licensed waste contractor. Advise highly flammable nature. If large amounts of the product enter waterways, sewers or streams, immediately contact the Environmental Protection Agency or your Local Waste Management Authority.

# Material Safety Data Sheet

Page 6 of 7

Issue date: December 2015

## STENCIL KING REDUCER

### 14. TRANSPORT INFORMATION

**Road Transport (ADR/RID):**

**UN Number:** 1993

**Proper Shipping Name:** FLAMMABLE LIQUID, N.O.S. (Contains 2-BUTOXY ETHANOL and ETHANOL)

**Dangerous Goods Class:** 3

**Packing Group:** II

**Air Transport (IATA):**

**UN Number:** 1993

**Proper Shipping Name:** FLAMMABLE LIQUID, N.O.S. (Contains 2-BUTOXY ETHANOL and ETHANOL)

**Dangerous Goods Class:** 3

**Packing Group:** II

**Sea Transport (IMDG):**

**UN Number:** 1993

**Proper Shipping Name:** FLAMMABLE LIQUID, N.O.S. (Contains 2-BUTOXY ETHANOL and ETHANOL)

**Dangerous Goods Class:** 3

**Packing Group:** II

**EmS:** F-E,S-D

### 15. REGULATORY INFORMATION

**Poison Schedule:** S5 [Aust]

This material is a Scheduled **S5** Poison and must be stored, handled and used according to the appropriate regulations.

**Inventory Status:**

Australia (AICS)	Y
United States (TSCA)	Y
Europe (EINECS/ELINCS)	Y

Y = all ingredients are on the inventory.

**EU Label:** Harmful (Xn), Irritant (Xi), Highly Flammable (F)

### 16. OTHER INFORMATION

**Date of Preparation:**

**Issue date:** December 07, 2015

**Supersedes:** August 08, 2011

**Reasons for Update:**

1. Review of fields and data, promoting uniformity of MSDS.
2. Changes to Sections 2, 4, 6, 8, 11, 15 & 16, based upon SUSDP first aid information.

**Key Legend Information:**

NOHSC - National Occupational Health & Safety Commission {Formerly Worksafe}[Aust]

ASCC - Australian Safety and Compensation Council [Aust]

SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons [Aust]

TWA - Time Weighted Average [Int]

STEL - Short Term Exposure Limit [Int]

AICS - Australian Inventory of Chemical Substances

Dangerous Goods - Initial Emergency Response Guide (SAA/SNZ HB76:2004) [Aust]

EPA - Environmental Protection Agency [Int]

NIOSH - National Institute for Occupational Safety and Health [US]

# Material Safety Data Sheet

Page 7 of 7

Issue date: December 2015

## STENCIL KING REDUCER

### 16. OTHER INFORMATION (continued)

TSCA - Toxic Substances Control Act [US]

OSHA - Occupational Safety and Health Administration [US]

AS/NZS 1715 - Selection, use and maintenance of respiratory protective devices. [Aust/NZ]

AS/NZS 1716 - Respiratory protective devices. [Aust/NZ]

Hazchem Code - Fire fighters designation [Aust]

IATA - International Aviation Transport Authority [Int]

ICAO - International Civil Aviation Organization [Int]

IMO - International Maritime Organisation. [Int]

IMDG - International Maritime Dangerous Goods [Int]

United Nations Recommendations for the Transport of Dangerous Goods and Globally Harmonized System for the classification and labelling of Chemicals. [Int]

EINECS - European Inventory of Existing Commercial Chemical Substances. [Int]

ELINCS - European List of Notified Chemical Substances. [Int]

EU - European Union [Int]

ADR/RID - European Road & Rail Transport Union - [Int]

**EU Directives:** The classification criteria used, are adopted from the European Community's (EC) legislation for classifying dangerous substances. The criteria are taken from:

EC Council Directive 67/548/EEC

EC Council Directive 1999/45/EC

[Aust/NZ] = Australian New Zealand

[Int] = International

[US] = United States of America

#### **Principal References:**

Information supplied by manufacturer, reference sources including the public domain.

#### **Disclaimer**

Any advice, recommendation, information, assistance or service provided by Dyepac Liquid Inks Pty. Ltd. in relation to the goods supplied by it or their use or application is given in good faith and believed to be appropriate and reliable, however, it is provided with a disclaimer for any liability or responsibility on the part of Dyepac Liquid Inks Pty. Ltd. The customer accepts all risk and responsibility for use of the goods alone, or in combination with other products. All warranties, guarantees and conditions, other than those expressly stated and whether implied by statute, common law, custom of the trade or otherwise, are to the extent that the law permits, expressly excluded.

**END OF MSDS**